

Formolene® L62009B

Linear Low Density Polyethylene (LLDPE) Resin Hexene Copolymer for Film Extrusion Applications

Formolene[®] L62009B is a general-purpose film grade linear low density made using gas-phase technology. The resin exhibits excellent toughness and strength when drawn down to thin gauges.

Formolene® L62009B meets all requirements of the U.S. Food and Drug Administration as specified in 21 CFR 177.1520, covering safe use of polyolefin articles intended for direct food contact.

Suggested Applications:

Blending Resin Industrial Packaging Co-Extrusion

Industrial Liners Garment Bags

Nominal Physical Properties:

i tommu i nysicui i topei dest						
	ASTM					
	TEST					
PROPERTY	METHOD	UNIT	VALUE			
Density	D1505	g/cc	0.919			
Melt Index, Condition E,	D1238	g/10	0.95			
190°C/2.16 kg		min.				
Dart Impact	D1709	g/mil.	160			
Tear Strength	D1922	g/mil.	400/630*			
Tensile Strength at Break	D882	psi.	4,750/3,485*			
Elongation	D882	%	520/780*			
Gloss, 45°	D523		33			
Haze	D1003	%	21			
* MD / TD						

Available in the following additive packages:

Additive	L62009A	L62009B	L62009H	L62009E2	L62009X
Antiblock (ppm)	7000	None	None	7000	None
Slip (ppm)	None	None	None	1500	None
Special	Additives	-	High	Additives	High
	talc based		Antioxidant	talc based	Antioxidant

Note: Film Properties based on 25 Micron blown film produced with a 2.5:1Blow Up Ratio. Actual film properties may vary depending on operating conditions and additive packages. Film properties are not intended to be used as specifications.

Published 08/01/04, Revised 01/11/16

Any inquiries regarding this data sheet should be addressed to: 9 Peach Tree Hill Road • Livingston, NJ 07039 • Phone: (888) FPCUSA3 • Fax: (973) 422-7772

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions concerning uses or applications are only the opinion of FORMOSA PLASTICS CORPORATION, U.S.A. The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions concerning uses or applications are only the opinion of FORMOSA PLASTICS CORPORATION, U.S.A. and users should perform their own tests to determine the usubability of these products for their own particular purposes. However, because of numerous factors affecting the results, FORMOSA PLASTICS CORPORATION, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, other than that the material conforms to the applicable current Standard Specifications Statements herein, therefore, should not be construed as representations or warranties. The responsibility of FORMOSA PLASTICS CORPORATION, U.S.A. for claims arising out of breach of warranty, negligence, strict liability or otherwise is limited to the purchase price of the material. Statements concerning the use of the products of formulations described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed.

© Formosa Plastics Corporation, U.S.A.